

Durata™

Defibrillation Leads with SJ4 Connector

MODELS 7120Q, 7121Q, 7122Q, 7170Q, 7171Q, 7172Q



SPECIFICATIONS

- The SJ4 connector is designed to simplify implants by streamlining defibrillation connections into a single terminal pin and reducing the number of set screws. The SJ4 connection reduces pocket bulk, which may provide increased comfort, particularly for patients who are thin or small in stature, and could lessen the risk of lead-to-can abrasion, a known complication.
- Redundant conductors, incorporated into the design, serve as a backup system in the unlikely event of a conductor failure.
- Symmetrically aligned cables within the lead body and centrally located coil provide for additional protection to the inner coil. Oversized lumens for cables allow effective absorption of external forces, e.g., clavicular crush.
- Optim™ insulation, a first-of-its-kind hybrid insulation material developed specifically for cardiac lead use, blends the biostability and flexibility of high-performance silicone rubber with the strength, tear resistance and abrasion resistance of polyurethane.
- Two innovative designs are intended to help prevent tissue ingrowth.
 - Flat-wire technology provides a low profile for the defibrillation coils.
 - Silicone backfilling completely fills the shock coil space.
- Steroid elution is designed to reduce inflammation at the lead-tissue interface resulting in lower acute and chronic stimulation thresholds.
- Small diameter lead—thinner than any competitive lead on the market—offers improved ease of venous passage, reduced risk of venous thrombosis or rib-clavicle crush, and enhanced ability to accommodate additional leads.
 - Built on the reliable Riata™ lead platform, the lead features design characteristics intended to enhance lead durability.
- Soft silicone tip* offers more compliance at the lead tip-endocardium interface.
 - Silicone tip profile in Durata family leads has been increased by greater than 60% over predecessor leads, but still passes through a 7 F introducer due to the material's soft nature.
 - Four pads on the silicone tip further increase the surface area of the lead tip that is in contact with the tissue.
- Slightly curved RV shock coil is designed to help reduce pressure at the lead tip-endocardium interface.
- Lubricious Fast-Pass™ coating facilitates lead insertion through the introducer and veins to ease implantation.
 - Fast-Pass coating helps reduce lead body surface friction allowing multiple leads to easily move against one another and reducing the chance of inadvertently moving one lead during the manipulation of another.
- Two different tip-to-proximal shock coil spacing options help to promote an effective shocking vector by allowing proper positioning of the proximal coil across a wide range of cardiac shapes and sizes.
- Dual- or single-shock coil models give physicians the option to choose the configuration that is best for each patient.
- Multiple lead lengths—52, 58, and 65 cm—afford physicians the flexibility to address the needs of patients with varying physical statures and vascular anatomies.
- Limited Lifetime Warranty.
 - Terms and Conditions Apply. Refer to the Warranty for Details.

*Active-fixation leads only.



ST. JUDE MEDICAL™

MORE CONTROL. LESS RISK.

PHYSICAL SPECIFICATIONS

True Bipolar, Active-Fixation Defibrillation Leads

Models	7120Q	7121Q	7122Q
Fixation	Ext/Ret Helix		
Shock Configuration	Dual-Coil		Single-Coil
Sensing Configuration	True Bipolar		
Min. Size Introducer	7 F		
Lengths	52, 58, 65 cm		
Body Diameter	6,8 F		
Tip-to-Anode Spacing	11 mm		
Tip-to-Proximal Coil	17 cm	21 cm	N/A
Tip Electrode Area	6 mm ²		
Steroid Plug	Yes		
Distal Shock Coil Area	367 mm ²		
Proximal Shock Coil Area	588 mm ²		N/A

True Bipolar, Passive-Fixation Defibrillation Leads

Models	7170Q	7171Q	7172Q
Fixation	Tines		
Shock Configuration	Dual-Coil		Single-Coil
Sensing Configuration	True Bipolar		
Min. Size Introducer	7 F		
Lengths	52, 58, 65 cm		
Body Diameter	6,8 F		
Tip-to-Anode Spacing	11 mm		
Tip-to-Proximal Coil	17 cm	21 cm	N/A
Tip Electrode Area	3.5 mm ²		
Steroid Plug	Yes		
Distal Shock Coil Area	367 mm ²		
Proximal Shock Coil Area	588 mm ²		N/A

ATRIAL FIBRILLATION CARDIAC RHYTHM MANAGEMENT CARDIAC SURGERY CARDIOLOGY NEUROMODULATION

Global Headquarters

One Lillehei Plaza
St. Paul, Minnesota 55117
USA
+1 651 483 2000
+1 651 490 4310 Fax

Cardiac Rhythm

Management Division
15900 Valley View Court
Sylmar, California 91342
USA
+1 818 362 6822
+1 818 364 5814 Fax

St. Jude Medical Sweden AB

Veddestavägen 19
175 84 Järfälla
Sweden
+46 8 474 40 00
+46 8 760 95 42 Fax

St. Jude Medical

Coordination Center BVBA
The Corporate Village
Da Vincilaan 11 Box F1
1935 Zaventem
Belgium
+32 2 774 68 11
+32 2 772 83 84 Fax

St. Jude Medical Brasil Ltda.

Rua Frei Caneca, 1380
7º ao 9º andares
01307-002 - São Paulo (SP)
Brazil
+55 11 5080 5400
+55 11 5080 5423 Fax

St. Jude Medical (Hong Kong) Ltd.

Unit 2701-07 27/F, COSCO Tower
Grand Millennium Plaza
183 Queen's Road
Central, Hong Kong
+852 2996 7688
+852 2956 0622 Fax

St. Jude Medical Japan Co., Ltd.

3-1-30, Minami-Aoyama
Minato-ku
Tokyo 107 0062
Japan
+81 3 3423 6450
+81 3 3402 5586 Fax

sjm.com



ST. JUDE MEDICAL™

MORE CONTROL. LESS RISK.

Brief Summary: Prior to using these devices, please review the Instructions for Use for a complete listing of indications, contraindications, warnings, precautions, potential adverse events and directions for use. Devices depicted may not be available in all countries. Check with your St. Jude Medical representative for product availability in your country. Unless otherwise noted, ™ indicates that the name is a trademark of, or licensed to, St. Jude Medical or one of its subsidiaries. ST. JUDE MEDICAL, the nine-squares symbol and MORE CONTROL. LESS RISK. are trademarks and service marks of St. Jude Medical, Inc. and its related companies. ©2009 St. Jude Medical, Inc. All Rights Reserved. Item GCMRME1677